



RENOLIT AGRICO

Applications and technical data

Oil tank protection

- flexible PVC film, polymer
- widths from 1,400 – 1,650 mm
- thickness: 750 μ

Pipe jackets

- rigid or semi-rigid PVC
- flame-retardant and twisted
- various widths and thicknesses available

Edges for false bottom plates

- rigid PVC
- high specific weight
- conductive and non-conductive
- thickness: 550 μ

Reverse printing film for office containers

- rigid PVC, translucent
- printable, can be laminated
- thickness: 100 μ

Pool liners

- rigid, translucent PVC
- printable, can be laminated
- thickness: 100 μ

Tie straps for tree nurseries

- flexible PVC film, opaque
- weather-proof
- thickness: from 100 - 240 μ
- width: 650 mm



Silage covers

- flexible PVC film, opaque
- weather-proof
- thickness: from 100 - 240 μ
- width: 650 mm

Wall covers

- flexible PVC film foam
- 90g wallpaper lacquered, printed, and coated with PVC is foamed by using a heating channel
- thickness: 800 μ
- width: 675 mm

Flakes flooring

- opaque and transparent soft PVC
- film has exactly balanced color and tint
- thickness from 100 – 200 μ
- various widths available

Drain covers

- flexible PVC film polymers
- film is oil- and weather-proof
- thickness from 500 - 1,000 μ
- diverse widths available