

RENOLIT ALKORPLAN⁸¹¹⁰⁷⁻⁰⁰²

Lightning conductor pads



SQUAD.BE

PRODUCT DESCRIPTION

Supplied as a one piece product, the lightning conductor pads have a reinforced **RENOLIT ALKORPLAN** base, which is fixed via a recessed rivet to a high grade polyethylene clip.

CHARACTERISTICS

Dimensions	100 mm x 100 mm
Colour	Lead grey
Reinforced membrane thickness	1.5 mm

FIELD OF APPLICATION

RENOLIT ALKORPLAN lightning conductor pads are the ideal solution for fixing neatly and securely flat conductor rod up to 25mm wide x 5mm thick. Overcome unsightly cover-straps which may lead to problems later or other incompatible or two part products.

INSTRUCTIONS FOR USE

The pad is simply hot air welded directly onto the field sheet.

PACKAGING

RENOLIT ALKORPLAN Lightning Conductor Pads are supplied in packs of 50 pieces.



This document replaces and supersedes all prior versions.

WWW.RENOLIT.COM/ROOFING

RENOLIT UK - Station Road, Cramlington, Northumberland NE23 8AQ - United Kingdom
T +44 1670 718283 - F +44 1670 718367 - matthew.adamson@renolit.com



Rely on it.

R2107EX0321