

RENOLIT ALKORPLUS⁸¹⁰⁰¹

Glass Fleece 120 g/m²



PRODUCT DESCRIPTION

RENOLIT ALKORPLUS Glass Fleece 120 g/m² is a nonwoven glass fibre separation and fire protection layer.

CHARACTERISTICS

Material	glass fibre nonwoven	
Colour	white	
Weight per area unit	120 g/m ²	DIN EN 299073-1
Thickness	1.34 mm	DIN EN ISO 9073-2

TECHNICAL PROPERTIES

Mechanical properties			
Tensile strength	MD	280 N/50 mm	DIN EN 29073-3
	CD	140 N/50 mm	DIN EN 29073-3
Binder content		7 %	DIN EN 13820

FIELD OF APPLICATION

- The **RENOLIT ALKORPLUS** glass fleece is used as a separation and fire protection layer between unbacked **RENOLIT ALKORPLAN**, **RENOLIT ALKORTEC** or **RENOLIT ALKORTOP** membranes and EPS/XPS insulation.

INSTALLATION

- The **RENOLIT ALKORPLUS** Glass Fleece is loose laid in accordance with **RENOLIT** installation instructions. Adjoining sheets overlap at least 50 mm.

PACKAGING

	Width	Length	Weight	Weight per roll
Delivery conditions	2 m	100 lm	120 g/m ²	24 kg/roll

STORAGE

- Rolls are singly packed and wrapped in polyethylene film.
- Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C.
- Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

WWW.RENOLIT.COM/ROOFING

RENOLIT Cramlington Ltd, Station Road - Cramlington, Northumberland NE23 8AQ - United Kingdom
T +44 1670 718283 - F +44 1670 719367 - renolit.cramlington@renolit.com

RENOLIT Belgium N.V. - Export Dpt. - Industriepark De Bruwaan 43 - 9700 Oudenaarde - Belgium
T +32 (0)55 33 98 51 - F +32 (0)55 31 86 58 - renolit.belgium@renolit.com



Rely on it.