

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: RENOLIT ALKORPLUS CONTACT ADHESIVE

81040

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Multiuse adhesive. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

RENOLIT IBERICA SA Ctra. del Montnegre, s/n

08470 Sant Celoni - Barcelona - España Phone: +34 938484000 - Fax: +34 938675936

renolit.iberica@renolit.com http://www.renolit.com/

1.4 Emergency telephone number: +44 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 2: Flammable liquids, Category 2, H225

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger





Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing spray.

P280: Wear protective gloves/eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

UFI: 4F00-E0QX-000K-4UJM

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 1/13

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of polymers and resins in solvent

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification		
CAS: 141-78-6 EC: 205-500-4	Ethyl acetate 1	ATP CLP00		
EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	⟨¹⟩ ⟨₫⟩	25 - <50 %
CAS: 78-93-3 EC: 201-159-0	Butanone 1		ATP CLP00	
EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	⟨¹⟩ ⟨₫⟩	25 - <50 %

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO).

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 2/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 5: FIREFIGHTING MEASURES (continued)

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 3/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 7: HANDLING AND STORAGE (continued)

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum time: 18 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification		Occupational exposure limits		
Ethyl acetate		IOELV (8h)	200 ppm	734 mg/m³	
CAS: 141-78-6	EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m³	
Butanone		IOELV (8h)	200 ppm	600 mg/m ³	
CAS: 78-93-3	EC: 201-159-0	IOELV (STEL)	300 ppm	900 mg/m³	

DNEL (Workers):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m³	1468 mg/m³	734 mg/m³	734 mg/m³
Butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m³	Non-applicable

DNEL (General population):

		Short e	exposure Long exposure		xposure
Identification		Systemic	Local	Systemic	Local
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m³	734 mg/m³	367 mg/m³	367 mg/m³
Butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m³	Non-applicable

PNEC:

Identification				
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 5/13



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation





Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	→	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 74 % weight
V.O.C. density at 25 °C: Non-applicable

Average carbon number: 4

Average molecular weight: 80,1 g/mol

SEC	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES				
9.1	Information on basic physical and chemical prope	rties:			
	For complete information see the product datasheet.				
	Appearance:				
	Physical state at 20 °C:	Liquid			
	Appearance:	Fluid			
	Colour:	White			
	Odour:	Solvent			
	Odour threshold:	Non-applicable *			
	Volatility:				
	Boiling point at atmospheric pressure:	>70 °C			
	Vapour pressure at 25 °C:	10330 Pa			
	Vapour pressure at 50 °C:	Non-applicable *			
	Evaporation rate at 25 °C:	Non-applicable *			
	Product description:				
	Density at 25 °C:	Non-applicable *			
	Relative density at 25 °C:	0,85 - 0,95			
	Dynamic viscosity at 25 °C:	1800 - 3200 cP			
	Kinematic viscosity at 25 °C:	Non-applicable *			
	Kinematic viscosity at 40 °C:	Non-applicable *			
	Concentration:	Non-applicable *			
	pH:	Non-applicable *			
	Vapour density at 25 °C:	>2,4 kg/m³			
	Partition coefficient n-octanol/water 25 °C:	Non-applicable *			
	Solubility in water at 25 °C:	Non-applicable *			
	Solubility properties:	Insoluble in water			
	Decomposition temperature:	Non-applicable *			
	Melting point/freezing point:	Non-applicable *			
	*Not relevant due to the nature of the product, not providing inform	nation property of its hazards.			

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 6/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability:

Flash Point:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable *
480 - 520 °C

Not available

Upper flammability limit:

Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Non-applicable *

Corrosive to metals:

Non-applicable *

Non-applicable *

Non-applicable *

Aerosols-total percentage (by mass) of flammable

Non-applicable *

components:

Surface tension at 25 °C:

Non-applicable *

Refraction index:

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

Other safety characteristics:

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 7/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability. Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Non-applicable

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Information on other hazards:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	Non-applicable	
Butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation	23,5 mg/L (4 h)	Rat

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Product-specific aquatic toxicity:

Acute toxicity		Species	Genus	
LC50	429,33 mg/L (96 h)	Non-applicable	Fish	
EC50	1256,97 mg/L (48 h)	Non-applicable	Crustacean	
EC50	3734,21 mg/L (72 h)	Non-applicable	Algae	

Substance-specific aquatic toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %
Butanone	BOD5	2,03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2,31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0,88	% Biodegradable	89 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
Ethyl acetate	BCF	30	
CAS: 141-78-6	Pow Log	0.73	
EC: 205-500-4	Potential	Moderate	
Butanone	BCF	3	
CAS: 78-93-3	Pow Log	0.29	
EC: 201-159-0	Potential	Low	

12.4 Mobility in soil:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Ethyl acetate	Koc	59	Henry	13,58 Pa·m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
Butanone	Koc	30	Henry	5,77 Pa·m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 10/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN113314.2 UN proper shipping name: ADHESIVES

14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: ||
14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: Non-applicable

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk according to IMO instruments:

Overland transport

Classification code (ADR) :F1
Special provisions (ADR) :640C
Limited quantities (ADR) :51
Excepted quantities (ADR) :E2
Packing instructions (ADR) :P001
Special packing provisions (ADR) :PP1
Mixed packing provisions (ADR) :MP19

Portable tank and bulk container instructions (ADR): T4

Portable tank and bulk container special provisions (ADR):TP1, TP8

Tank code (ADR) :L1.5BN
Vehicle for tank carriage :FL
Transport category (ADR) :3

Special provisions for carriage - Operation (ADR) :S2, S20 Hazard identification number (Kemler No.) :33

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



14.1 UN number or ID number: UN113314.2 UN proper shipping name: ADHESIVES

14.3Transport hazard class(es):3Labels:314.4Packing group:II14.5Marine pollutant:No14.6Special precautions for user

Special regulations:

EmS Codes:

Physico-Chemical properties:

Non-applicable
F-E, S-D
see section 9

Limited quantities: 5 L

Segregation group: Non-applicable

Maritime transport in bulk - Overland transport

according to IMO instruments: Classification code (ADR) :F1
Special provisions (ADR) :64/

Special provisions (ADR) :640C
Limited quantities (ADR) :51
Excepted quantities (ADR) :E2
Packing instructions (ADR) :P001
Special packing provisions (ADR) :PP1
Mixed packing provisions (ADR) :MP19

Portable tank and bulk container instructions (ADR): T4

Portable tank and bulk container special provisions (ADR) :TP1, TP8

Tank code (ADR) :L1.5BN
Vehicle for tank carriage :FL
Transport category (ADR) :3

Special provisions for carriage - Operation (ADR) :S2, S20 Hazard identification number (Kemler No.) :33

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN113314.2 UN proper shipping name: ADHESIVES

 14.3
 Transport hazard class(es):
 3

 Labels:
 3

 14.4
 Packing group:
 II

 14.5
 Environmental hazards:
 No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Maritime transport in bulk - Overland transport **according to IMO instruments:** Classification code (ADR)

Special provisions (ADR) :640C
Limited quantities (ADR) :51
Excepted quantities (ADR) :E2
Packing instructions (ADR) :P001
Special packing provisions (ADR) :PP1
Mixed packing provisions (ADR) :MP19

Portable tank and bulk container instructions (ADR): T4

Portable tank and bulk container special provisions (ADR):TP1, TP8

:F1

Tank code (ADR) :L1.5BN
Vehicle for tank carriage :FL
Transport category (ADR) :3

Special provisions for carriage - Operation (ADR) :S2, S20 Hazard identification number (Kemler No.) :33

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtravs.
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6) Page 12/13

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any countryspecific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81040



Date of compilation: 18/04/2016 Revised: 31/10/2023 Version: 7 (Replaced 6)

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Substances that contribute to the classification (SECTION 2):

· Removed substances

Ethyl acetate (141-78-6)

Butanone (78-93-3)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- · Pictograms
- · Hazard statements

Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

^{**} Changes with regards to the previous version