

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020	Revised: 05/08/2022	Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1 Product identifier: **RENOLIT ALKORPLUS** CONTACT ADHESIVE 81064 Other means of identification: Non-applicable 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Multiuse adhesive. For professional users only. Uses advised against: All uses not specified in this section or in section 7.3 1.3 Details of the supplier of the safety data sheet: **RENOLIT IBERICA SA** Ctra. del Montnegre, s/n 08470 Sant Celoni - Barcelona - España Phone: +34 938484000 - Fax: +34 938675936 renolit.iberica@renolit.com http://www.renolit.com/ 1.4

Emergency telephone number: +44 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 2: Flammable liquids, Category 2, H225 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Dange



Hazard statements:

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.

Revised: 05/08/2022

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- P233: Keep container tightly closed.
- P240: Ground and bond container and receiving equipment.
- P241: Use explosion-proof equipment.
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264: Wash thoroughly after handling.
- 2M00-F03Q-M00K-FHQR UFI:
- Other hazards: 23

Version: 3 (Replaced 2)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064



Date of compilation: 16/07/2020

Version: 3 (Replaced 2)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

Revised: 05/08/2022

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of polymers and resins in solvent

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification			
CAS: EC:	110-82-7 203-806-2	cyclohexane□¹□		ATP CLP00	
Index: 601-017-00-1 REACH: 01-2119463273-41- XXXX		Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger		20 - <30 %
CAS: EC:	64742-49-0 927-510-4	Hydrocarbons, C7, n-a	alkanes, isoalkanes, cyclics⊡¹⊟	Self-classified	
Index:	Non-applicable : 01-2119475515-33- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger		10 - <30 %
CAS:	141-78-6	Ethyl acetate 1		ATP CLP00	
EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46- XXXX Regulation 1272/2		Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	(!)	8 - <15 %
CAS: 64742-49-0		Hydrocarbons, C6, iso	oalkanes, <5% n-hexane□¹□	Self-classified	
	Non-applicable : 01-2119484651-34-	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger		5 - <15 %

□¹□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:


Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS CONTACT ADHESIVE 81064



Date of compilation: 16/07/2020

Version: 3 (Replaced 2)

SECTION 4: FIRST AID MEASURES (continued)

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Revised: 05/08/2022

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (COC).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

Advice for firefighters: 5.3

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 **Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

Methods and material for containment and cleaning up: 6.3

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064



Date of compilation: 16/07/2020

Version: 3 (Replaced 2)

SECTION 7: HANDLING AND STORAGE (continued)

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Revised: 05/08/2022

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

7.2

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification	Occupational exposure limits			
cyclohexane		IOELV (8h)	200 ppm	700 mg/m ³	
CAS: 110-82-7	EC: 203-806-2	IOELV (STEL)			
Ethyl acetate		IOELV (8h)	200 ppm	734 mg/m ³	
CAS: 141-78-6	EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³	

DNEL (Workers):

	Short e	xposure	Long exposure		
Identification	Systemic	Local	Systemic	Local	
cyclohexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	2016 mg/kg	Non-applicable
EC: 203-806-2	Inhalation	1400 mg/m ³	1400 mg/m ³	700 mg/m³	700 mg/m ³
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
EC: 927-510-4	Inhalation	Non-applicable	Non-applicable	2085 mg/m ³	Non-applicable



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation



RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

	Short e	exposure	exposure		
Identification	Systemic	Local	Systemic	Local	
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	13964 mg/kg	Non-applicable
EC: 931-254-9	Inhalation	Non-applicable	Non-applicable	5306 mg/m ³	Non-applicable

DNEL (General population):

		Short e	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
cyclohexane	Oral	Non-applicable	Non-applicable	59,4 mg/kg	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	1186 mg/kg	Non-applicable
EC: 203-806-2	Inhalation	412 mg/m ³	412 mg/m ³	206 mg/m ³	206 mg/m ³
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Oral	Non-applicable	Non-applicable	149 mg/kg	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	149 mg/kg	Non-applicable
EC: 927-510-4	Inhalation	Non-applicable	Non-applicable	447 mg/m³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m³	367 mg/m ³
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Oral	Non-applicable	Non-applicable	1301 mg/kg	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	1377 mg/kg	Non-applicable
EC: 931-254-9	Inhalation	Non-applicable	Non-applicable	1131 mg/m ³	Non-applicable

PNEC:

Identification				
cyclohexane	STP	3,24 mg/L	Fresh water	0,207 mg/L
CAS: 110-82-7	Soil	3,38 mg/kg	Marine water	0,207 mg/L
EC: 203-806-2	Intermittent	0,207 mg/L	Sediment (Fresh water)	16,68 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,68 mg/kg
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Spec ; p



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

! 🖄 🐮

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

				81064				
ate of com	pilation: 16/07/2020	0 1	Revised: 05/08/2	2022 Ver	rsion: 3	(Replaced 2)		
SECTIO	N 8: EXPOSUR	E CON	TROLS/PERS	SONAL PRO	TECTI	ON (continued)		
	Pictogram		PPE	Labelling	C	EN Standard		Remarks
	Mandatory hand protection	(Material: polyeth Breakth min, Thic	l protective gloves Linear low-density nylene (LLDPE), rough time: > 480 kness: 0.062 mm)			ISO 21420:2020		lace the gloves at any sign of deterioration.
D.	As the product is total reliability and - Eye and face prof	d has the					rial car	n not be calculated in advance with
	Pictogram		PPE	Labelling	C	EN Standard		Remarks
	Mandatory face protection		ic glasses against h/projections.			EN 166:2002 ISO 4007:2018		n daily and disinfect periodically according to nanufacturer's instructions. Use if there is a risk of splashing.
E.	- Body protection							
	Pictogram		PPE	Labelling	C	EN Standard		Remarks
	Mandatory complete body protection		tic and fireproof active clothing		EI EI EN	N 1149-1:2006 N 1149-2:1997 N 1149-3:2004 EN 168:2002 ISO 14116:2015 N 1149-5:2018		Limited protection against flames.
	Mandatory foot protection	antistatic	y footwear with and heat resistant properties			ISO 13287:2020 ISO 20345:2011	Re	eplace boots at any sign of deterioration.
F	F Additional emergency measures							
	Emergency mea	asure	Sta	andards		Emergency measu	ıre	Standards
	Emergency sho	ower		SI Z358-1 11, ISO 3864-4:20	011	Eyewash station	s	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
ln sp Vo	accordance with the illage of both the pro- platile organic con ith regard to Directi V.O.C. (Supply): V.O.C. density at Average carbon r Average molecula	e commu roduct ar npounds ve 2010/ 25 °C: number:	unity legislation f id its container. F :: 75/EU, this prod 65 % 552,5 6	or additional ir	nformation lowing cl	on see subsectior		mended to avoid environmental
	N 9: PHYSICAL							
	formation on basion on basion of complete information							
	opearance:							
-	ysical state at 20 °	C:		Liqui	iid			
	pearance:			Fluic				

*Not relevant due to the nature of the product, not providing information property of its hazards.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064



te of o	compilation: 16/07/2020 Revised: 05/08/2022	Version: 3 (Replaced 2)
SEC	TION 9: PHYSICAL AND CHEMICAL PROPER	RTIES (continued)
	Colour:	Blue
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	>35 ℃
	Vapour pressure at 25 °C:	16000 Pa
	Vapour pressure at 50 °C:	Non-applicable *
	Evaporation rate at 25 °C:	Non-applicable *
	Product description:	
	Density at 25 °C:	850 kg/m³
	Relative density at 25 °C:	Non-applicable *
	Dynamic viscosity at 25 °C:	Non-applicable *
	Kinematic viscosity at 25 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 25 °C:	>1 kg/m³
	Partition coefficient n-octanol/water 25 °C:	Non-applicable *
	Solubility in water at 25 °C:	Non-applicable *
	Solubility properties:	Immiscible
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	-26 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	>200 °C
	Lower flammability limit:	1,1 % Volume
	Upper flammability limit:	7,4 % Volume
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
.2	Other information:	
	Information with regard to physical hazard classe	s:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Non-applicable *
	Surface tension at 25 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing inforr	



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020 Revised: 05/08/2022 SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

Version: 3 (Replaced 2)

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Not applicable Not applicable Risk of combustion Avoid direct impact Not applicable	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

-				
Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (COD), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008: 11.1

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea

and vomiting. B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (3); Hydrocarbons, C6, isoalkanes, <5% n-hexane (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064



Date of compilation: 16/07/2020 Revised: 05/08/2022

2 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3. **Other information:**

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	Non-applicable	
cyclohexane	LD50 oral	5100 mg/kg	Rat
CAS: 110-82-7	LD50 dermal	Non-applicable	
EC: 203-806-2	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020

Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
cyclohexane	LC50	>0.1 - 1 (96 h)		Fish
CAS: 110-82-7	EC50	>0.1 - 1 (48 h)		Crustacean
EC: 203-806-2	EC50	>0.1 - 1 (72 h)		Algae
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LC50	>1 - 10 (96 h)		Fish
CAS: 64742-49-0	EC50	>1 - 10 (48 h)		Crustacean
EC: 927-510-4	EC50	>1 - 10 (72 h)		Algae
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Hydrocarbons, C6, isoalkanes, <5% n-hexane	LC50	Non-applicable		
CAS: 64742-49-0	EC50	3,87 mg/L (48 h)	Daphnia magna	Crustacean
EC: 931-254-9	EC50	55 mg/L (72 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	NOEC	Non-applicable		
CAS: 64742-49-0 EC: 927-510-4	NOEC	0,17 mg/L	Daphnia magna	Crustacean
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	De	egradability	Biodegradability	
cyclohexane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 110-82-7	COD	Non-applicable	Period	28 days
EC: 203-806-2	BOD5/COD	Non-applicable	% Biodegradable	0 %
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 64742-49-0	COD	Non-applicable	Period	14 days
EC: 927-510-4	BOD5/COD	Non-applicable	% Biodegradable	95 %
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020 Revised: 05/08/2022

2 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Deç	gradability	Biodegradability	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64742-49-0	COD	Non-applicable	Period	28 days
EC: 931-254-9	BOD5/COD	Non-applicable	% Biodegradable	98 %

12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential		
cyclohexane	BCF		66	
CAS: 110-82-7	Pow L	.og	3.44	
EC: 203-806-2	Potent	tial	Moderate	
Ethyl acetate	BCF		30	
CAS: 141-78-6	Pow L	.og	0.73	
EC: 205-500-4	Potent	tial	Moderate	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	BCF		501	
CAS: 64742-49-0		og	3.6	
EC: 931-254-9	Potent	tial	High	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
cyclohexane	Koc	Non-applicable	Henry	Non-applicable
CAS: 110-82-7	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-806-2	Surface tension	2,465E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethyl acetate	Koc	59	Henry	13,58 Pa⋅m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020	Revised: 05/08/2022 V	ersion: 3 (Replaced 2)
SECTION 14: TRANSPOR	T INFORMATION	
Transport of dangerou With regard to ADR 202		
14.1 14.2 14.2 14.3	UN number or ID number: UN proper shipping name: Transport hazard class(es):	UN1133 ADHESIVES 3
14.4	Labels: Packing group:	3
14.5	Environmental hazards:	Yes
14.6	Special precautions for user Special regulations: Tunnel restriction code: Physico-Chemical properties: Limited quantities:	Non-applicable D/E see section 9 500 mL
14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of dangerou	•	
With regard to IMDG 40	9-20:	
14.1	UN number or ID number:	UN1133
14.2	UN proper shipping name: Transport hazard class(es): Labels:	ADHESIVES 3 3
14.4	Packing group:	I
14.5	Marine pollutant:	Yes
14.6	Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities:	Non-applicable F-E, S-D see section 9 500 mL
14.7	Segregation group: Maritime transport in bulk according to IMO instruments:	Non-applicable Non-applicable
Transport of dangerou	0	
With regard to IATA/ICA		
14.1 14.2 14.3	UN number or ID number: UN proper shipping name: Transport hazard class(es):	UN1133 ADHESIVES 3
• •	Labels:	3
14.4 14.5 14.6	Packing group: Environmental hazards: Special precautions for user Physico-Chemical properties:	Yes see section 9
14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

- CONTINUED ON NEXT PAGE -

Document generated with Chemeter (www.siam-it.com)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation



RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020

Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION (continued)

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc) :

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:



Rely on it.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81064

Date of compilation: 16/07/2020 Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -