

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 11 Product identifier: **RENOLIT - ALKORPLUS SANITIZATION** 81052-002 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Disinfectant . For professional use only Uses advised against: All uses not specified in this section or in section 7.3 1.3 Details of the supplier of the safety data sheet: RENOLIT Ibérica, SA Carretera del Montnegre s/n E-08470 Sant Celoni (Barcelona) España +34 93 848 4264 Tfno · Fax. +34 93 867 5936 renolit.iberica@renolit.com www.renolit.com +44 1235 239 670 Emergency telephone number: 1.4 SECTION 2: HAZARDS IDENTIFICATION 2.1 Classification of the substance or mixture: CLP Regulation (EC) nº 1272/2008: Classification of this product has been carried out in accordance with CLP Regulation (EC) nº 1272/2008. Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302 Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Eye Dam. 1: Serious eye damage, Category 1, H318 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Corr. 1B: Skin corrosion, Category 1B, H314 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336 Label elements: 2.2 CLP Regulation (EC) nº 1272/2008: Danger Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed Aquatic Acute 1: H400 - Very toxic to aquatic life Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Corr. 1B: H314 - Causes severe skin burns and eye damage STOT SE 3: H336 - May cause drowsiness or dizziness

# Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P280: Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P370+P378: In case of fire: Use ABC powder extinguisher to extinguish. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

# Substances that contribute to the classification

Didecyldimethylammonium chloride; Propan-2-ol

# 2.3 Other hazards:

Non-applicable



## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

**Chemical description:** Not defined

#### Components:

In accordance with Annex II of Regulation (EC) nº1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	7173-51-5	Didecyldimethylammonium chloride	ATP CLP00	
	230-525-2 612-131-00-6 : 01-2119945987-15-XXXX	Regulation 1272/2008 Acute Tox. 4: H302; H314 - Danger	Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Skin Corr. 1B:	50 - <75 %
CAS:	67-63-0	Propan-2-ol	ATP CLP00	
	200-661-7 603-117-00-0 : 01-2119457558-25-XXXX	Regulation 1272/2008 Eye Irrit. 2: H319; Fla	im. Liq. 2: H225; STOT SE 3: H336 - Danger	10 - <25 %
		tion on the risk of the substances of	onsult sections 8, 11, 12, 15 and 16.	1

# SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Keep the person affected at rest.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

#### Special hazards arising from the substance or mixture: 5.2

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### Advice for firefighters: 5.3



# SECTION 5: FIREFIGHTING MEASURES (continue)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

# 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

#### A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C	С
Maximum Temp.: 30	°C
Maximum time: 6 M	lonths



## SECTION 7: HANDLING AND STORAGE (continue)

# B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

# 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no environmental limits for the substances contained in the product

#### DNEL (Workers):

		Short e	xposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
Didecyldimethylammonium chloride	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7173-51-5	Dermal	Non-applicable	Non-applicable	8,6 mg/kg	Non-applicable
EC: 230-525-2	Inhalation	Non-applicable	Non-applicable	18,2 mg/m³	Non-applicable
Propan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	500 mg/m³	Non-applicable

#### DNEL (General population):

		Short e	kposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
Propan-2-ol	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	89 mg/m³	Non-applicable

#### PNEC:

Identification				
Didecyldimethylammonium chloride	STP	0,595 mg/L	Fresh water	0,002 mg/L
CAS: 7173-51-5	Soil	1,4 mg/kg	Marine water	0,0002 mg/L
EC: 230-525-2	Intermittent	0,00029 mg/L	Sediment (Fresh water)	2,82 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,28 mg/kg
Propan-2-ol	STP	2251 mg/L	Fresh water	140,9 mg/L
CAS: 67-63-0	Soil	28 mg/kg	Marine water	140,9 mg/L
EC: 200-661-7	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	160 g/kg	Sediment (Marine water)	552 mg/kg

## 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### **B.-** Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory hand protection		isposable chemical otective gloves		EN 3	EN 374-1:2003 74-3:2003/AC:2006 420:2003+A1:2009	manu the	The Breakthrough Time indicated by the facturer must exceed the period during whicl product is being used. Do not use protective s after the product has come into contact wit skin.
D (	Ocular and facial p	protection	<u></u>		•			
	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory face protection		Face mask	CATI	E	EN 166:2001 EN 167:2001 EN 168:2001 N ISO 4007:2012		daily and disinfect periodically according to th facturer 's instructions. Use if there is a risk o splashing.
E E	Bodily protection				•			
Γ	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory complete body protection	protection risks, v	sable clothing for on against chemical with antistatic and proof properties		EN ISO El El	EN 1149-1,2,3 3034:2005+A1:2009 13982-1:2004/A1:2010 V ISO 6529:2001 V ISO 6530:2005 I ISO 13688:2013 EN 464:1994	aco	or professional use only. Clean periodically cording to the manufacturer 's instructions.
	Mandatory foot protection	against	otwear for protection chemical risk, with c and heat resistant properties		EN	EN 13287:2008 I ISO 20345:2011 N 13832-1:2006	R	eplace boots at any sign of deterioration.
F A	Additional emerge	ncy mea	sures					
Γ	Emergency mea	asure	Sta	indards		Emergency measu	ire	Standards
	Emergency sho	wer		I Z358-1 864-1:2002		Eyewash station:	S	DIN 12 899 ISO 3864-1:2002
Envi	ironmental exp	osure co	ontrols:					
of bo		nd its cor	ntainer. For additio				ecomm	nended to avoid environmental spilla
With	regard to Directi	ve 2010/	75/EU, this produc	t has the follo	owina ch	aracteristics:		
					5			

V.O.C. (Supply):	20 % weight
V.O.C. density at 20 °C:	183,94 kg/m³ (183,94 g/L)
Average carbon number:	3
Average molecular weight:	60,1 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	
---	--

# 9.1 Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: \*Not relevant due to the nature of the product, not providing information property of its hazards.



SECTION 9: PHYSICAL AND CHEMICAL PROPE	RTIES (continue)
Color:	Colourless
Odor:	Alcohol
Volatility:	
Boiling point at atmospheric pressure:	92 °C
Vapour pressure at 20 °C:	2808 Pa
Vapour pressure at 50 °C:	14585 Pa (15 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	920 kg/m³
Relative density at 20 °C:	0,92
Dynamic viscosity at 20 °C:	2,64 cP
Kinematic viscosity at 20 °C:	2,87 cSt
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	26 °C
Autoignition temperature:	399 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *
*Not relevant due to the nature of the product, not provid	ting information property of its hazards.

10.1	Reactivity:								
	No hazardous reactions are e	expected because the pr	oduct is stable under recomn	nended storage condition	s. See section 7.				
10.2	Chemical stability:								
	Chemically stable under the conditions of storage, handling and use.								
10.3	Possibility of hazardous reactions:								
	Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.								
10.4	Conditions to avoid:								
	Applicable for handling and storage at room temperature:								
	Applicable for handling and s	torage at room tempera	ature:						
	Applicable for handling and s Shock and friction	torage at room tempera Contact with air	ture:	Sunlight	Humidity				
		5		Sunlight Avoid direct impact	Humidity Not applicable				
10.5	Shock and friction	Contact with air	Increase in temperature	5					
10.5	Shock and friction Not applicable	Contact with air	Increase in temperature	5					



# SECTION 10: STABILITY AND REACTIVITY (continue)

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- Corrosivity/Irritability: Corrosive product, its consumption causes burns destroying the full thickness of fabrics. For more information on the secondary effects of contact with the skin see section 2.

B- Inhalation:

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes:

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.

- Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensibilizising effects. For more information see section 3.

- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT)-time exposure:

Exposure in high consciousnesss can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Non-applicable

# Specific toxicology information on the substances:



# SECTION 11: TOXICOLOGICAL INFORMATION (continue)

Identification	A	Acute toxicity		
Propan-2-ol	LD50 oral	5280 mg/kg	Rat	
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat	
EC: 200-661-7	LC50 inhalation	72,6 mg/L (4 h)	Rat	
Didecyldimethylammonium chloride	LD50 oral	500 mg/kg	Rat	
CAS: 7173-51-5	LD50 dermal	Non-applicable		
EC: 230-525-2	LC50 inhalation	Non-applicable		

#### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification	Acute toxicity		Specie	Genus
Didecyldimethylammonium chloride	LC50	0,33 mg/L (96 h)	Pimephales promelas	Fish
CAS: 7173-51-5	EC50	0,06 mg/L (48 h)	Daphnia magna	Crustacean
EC: 230-525-2	EC50	Non-applicable		
Propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-661-7	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

# 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Didecyldimethylammonium chloride	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 7173-51-5	COD	Non-applicable	Period	28 days
EC: 230-525-2	BOD5/COD	Non-applicable	% Biodegradable	0 %
Propan-2-ol	BOD5	1.19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2.23 g O2/g	Period	14 days
EC: 200-661-7	BOD5/COD	0.53	% Biodegradable	86 %

# 12.3 Bioaccumulative potential:

Identification	Bioac	Bioaccumulation potential		
Didecyldimethylammonium chloride	BCF	81		
CAS: 7173-51-5	Pow Log	4,66		
EC: 230-525-2	Potential	Moderate		
Propan-2-ol	BCF	3		
CAS: 67-63-0	Pow Log	0,05		
EC: 200-661-7	Potential	Low		

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Didecyldimethylammonium chloride	Кос	440000	Henry	Non-applicable
CAS: 7173-51-5	Conclusion	Immobile	Dry soil	Non-applicable
EC: 230-525-2	Surface tension	Non-applicable	Moist soil	Non-applicable
Propan-2-ol	Кос	1,5	Henry	8,207E-1 Pa∙m <sup>3</sup> /mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	22400 N/m (25 °C)	Moist soil	Yes

# 12.5 Results of PBT and vPvB assessment:

Non-applicable

# 12.6 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS



# SECTION 13: DISPOSAL CONSIDERATIONS (continue)

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
07 04 04*	Other organic solvents, washing liquids and mother liquors	Dangerous	

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP6 Acute Toxicity, HP8 Corrosive

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:

	14.1	UN number:	UN2920		
	14.2	UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Didecyldimethylammonium chloride; Propan-2-ol)		
$\mathbf{\nabla}$	14.3	Transport hazard class(es):	8		
		Labels:	8, 3		
<u>〈<u>も</u>〉</u>	14.4	Packing group:	II		
$\sim$	14.5	Dangerous for the environment:	Yes		
	14.6	Special precautions for user			
		Special regulations:	274		
		Tunnel restriction code:	D/E		
		Physico-Chemical properties:	see section 9		
		Limited quantities:	1 L		
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable		
Transport of dar	ngerou	us goods by sea:			
With regard to IMI	With regard to IMDG 37-14:				



SECTION 14: TRANS	PORT	INFORMATION (continue)	
	14.1	UN number:	UN2920
	14.2	UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Didecyldimethylammonium chloride; Propan-2-ol)
	14.3	Transport hazard class(es):	8
× ×		Labels:	8, 3
44	14.4	Packing group:	II
	14.5	Dangerous for the environment:	Yes
	14.6	Special precautions for user	
		Special regulations:	274, 944
		EmS Codes:	F-E, S-C
		Physico-Chemical properties:	see section 9
		Limited quantities:	1 L
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of d	langero	us goods by air:	
With regard to I	ATA/ICA	AO 2015:	
		UN number: UN proper shipping name:	UN2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Didecyldimethylammonium chloride; Propan-2-ol)
	14.3	Transport hazard class(es):	8
< 1 <u>4</u> 2		Labels:	8, 3
$\sim$	14.4	Packing group:	II
	14.5	Dangerous for the environment:	Yes
	14.6	Special precautions for user	
		Physico-Chemical properties:	see section 9
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

## SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Didecyldimethylammonium chloride.

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Didecyldimethylammonium chloride (Product-type 1, 2, 3, 4, 6, 8, 10, 11, 12); Propan-2-ol (Product-type 1, 2, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Didecyldimethylammonium chloride

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):

Non-applicable

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:



# SECTION 15: REGULATORY INFORMATION (continue)

The supplier has not carried out evaluation of chemical safety.

# SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

#### Modifications related to the previous security card which concerns the ways of managing risks. :

## COMPOSITION/INFORMATION ON INGREDIENTS:

- Added Content
  - Didecyldimethylammonium chloride (7173-51-5)
- · Removed Content
- Didecyldimethylammonium chloride (7173-51-5)
- CLP Regulation (EC) nº 1272/2008:
  - · Pictograms
  - Hazard statements

#### Texts of the legislative phrases mentioned in section 2:

- H318: Causes serious eye damage
- H400: Very toxic to aquatic life
- H411: Toxic to aquatic life with long lasting effects
- H336: May cause drowsiness or dizziness
- H302: Harmful if swallowed
- H226: Flammable liquid and vapour
- H314: Causes severe skin burns and eye damage

# Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) nº 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed Aquatic Acute 1: H400 - Very toxic to aquatic life Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Skin Corr. 1B: H314 - Causes severe skin burns and eye damage STOT SE 3: H336 - May cause drowsiness or dizziness

#### Classification procedure:

Eye Dam. 1: Calculation method Aquatic Acute 1: Calculation method Aquatic Chronic 2: Calculation method STOT SE 3: Calculation method Acute Tox. 4: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Skin Corr. 1B: Calculation method

#### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

## Principal bibliographical sources:

http://esis.jrc.ec.europa.eu http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:



# SECTION 16: OTHER INFORMATION (continue)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.