

TECHNICAL DATA SHEET

RENOLIT ALKORPLUS VOGUE SEAM FINISH - Type 81020

Application:

Reinforcement of welded joints, T-borders and corners for RENOLIT ALKORPLAN Vogue varnished waterproofing membranes.

Technical Data:

- Base: Solution of vinyl resins and acrylic in MEK (methyl ethyl ketone)
- Color: Variable
- Viscosity: Approx. 2.500 mPa·s
- Solid Content: Approx. 18-23 %
- Specific Density: Approx. 0,9 g/cm³
- Flash Point: < 21°C (Highly flammable liquid and vapors)
- Toxicity: Causes serious eye irritation. May cause drowsiness or dizziness.

Placement:

For swimming pool membranes. Use polyethylene bottle to apply a 3-5 mm wide sealing of seams. Protect it against frost. Dilute only with MEK or THF. SHAKE WELL BEFORE USE. Let dry for at least 2 hours before filling the swimming pool.

Packaging:

Metallic Cans of 900 g. Six cans in a box.

Shelf Life:

3 years.

Consumption:

Approx. 1 kg/100 m

Caution:

As it is flammable product, one must avoid closeness to fire, flames and sparks during its storage and usage, hence it is to be used in well-ventilated areas. Do not smoke during its application. Do not use the product at temperatures below 10°C. Causes serious eye irritation. May cause drowsiness or dizziness. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use foam or dry powder for extinction.

Storage:

Follow the instructions relating to inflammable products, refer to the text on the label and take into consideration the data given on the safety sheet, which is available on request.

For more information:

Read MSDS.