

TECHNICAL DATA SHEET

RENOLIT ALKORPLUS SEAM SEALER- Types 81028 / 81029 / 81032 / 81034 / 81035 / 81037 / 81039 / 81049 / 81050 / 81054

Application:

Reinforcement of welded joints, T-borders and corners for RENOLIT ALKORPLAN waterproofing membranes.

Technical Data:

- Base: Solution of polyvinyl chloride (PVC) in Tetrahydrofuran (THF).
- Color: Variable
- Viscosity: Approx. 1.000 cP
- Solid Content: Approx. 18-23 %
- Specific Density: Approx. 0,94 g/cm³
- Flash Point: -15 C (< 21°C; Highly flammable liquid and vapors)
- Toxicity: Causes serious eye irritation. May cause drowsiness or dizziness.

Placement:

For swimming pool membranes. Use polyethylene bottle to apply a 3-5 mm wide sealing of seams. Protect it against frost. Dilute the product if necessary, only with THF. SHAKE WELL BEFORE USE. Let dry for at least 2 hours before filling the swimming pool.

Packaging:

Metallic Cans of 900 g. Six cans in a box.

Shelf Life:

3 years.

Consumption:

Approx. 1 kg/100 m

Caution:

As it is flammable product, one must avoid closeness to fire, flames and sparks during its storage and usage, hence it is to be used in well-ventilated areas. Do not smoke during its application. Keep container tightly closed. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

Store in well-ventilated areas.

For more information:

Read MSDS.